

FOOD GRADE RUBBER HOSE

VPS CUVÉE

General-purpose suction and discharge hose for food and beverage processing.

White Chlorobutyl (FDA, 3-A, USDA compliant) tube with reinforcement from spiral plied synthetic fabric with Polyester Monofilament Helix. Cover is gray (wrapped) / white & green branding tape.



GATES CELLAR MASTER

Also available.

FOOD GRADE PVC HOSE

NUTRIFLO

General-purpose suction and discharge hose for food processing.

Clear Pliovic (FDA, 3-A, USDA compliant) tube with reinforcement from high density Pliovic helix.



KANALINE FW

Heavy duty food grade suction and discharge hose.

Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated OD (FDA & 3-A compliant). Lightweight and flexible with clear sidewall permits visual check of material flow. External helix provides easy drag.



BRAND	ID SIZE (in)	MAX. WP	VACUUM	TEMPERATURE
VPS Cuvée	1, 1-1/2, 2, 2-1/2, 3	250psi	27 in/HG	-30° F to 220° F
Nutriflo	1	106 psi	29 in/HG	15° F to 150° F
	1-1/2	89 psi		
	2	79 psi		
	3	65 psi		
	4	55 psi		
Kanaline FW	1-1/2, 2, 3	125 psi	28 in/HG	-13° F to 158° F
	4	100 psi		
<i>Washdown</i>	1/2, 1	300 psi	---	-20° F to 190° F

WASHDOWN RUBBER HOSE

ECONOMICAL AIR & WATER HOSE

Red or white synthetic rubber tube with spiral synthetic yarn reinforcement.



A wide variety of shanks available, designed to prevent slippage and blow off.